

LETATWIN

MAX



LM-550A/PC

Tube and Tape Printer for Electrical Marking

►► *Professional Grade*



PC
CONNECT



40mm
SEC
HIGH SPEED



INK RIBBON

110m



WHITE TAPE

16m



REFILL TYPE

INK



CARRY CASE




INTEGRATED
KEY BOARD



BACKLIT

LARGE
LCD



ELECTRICAL
SYMBOLS



LARGE RAM

250,000
CHARACTERS



USB

DATA
EXCHANGE



SERIAL
NUMBER

1,2,3..



HALF CUT

ADJUSTABLE
DEPTH OF CUT



HEAT SHRINK
TUBE OK



PREVIEW



ADJUSTABLE
PITCH



WORDS




COPY & PASTE

PC Connection

Easy data input from your PC
for wire marking solutions!



LETATWIN PC EDITOR Easy Operation : Copy & Paste



SIMPLE STEPS TO INSTALL SOFTWARE AND PRINTER DRIVER TO YOUR PC

Step 1: Setup the LETATWIN PC editor

- Insert the included CD ROM into your computer and click "Setup_Letatwin.exe".
- Select "Setup of the LETATWIN PC EDITOR"

Step 2: Install the printer driver

- Connect the LM-550A/PC to your computer with a USB cable, then turn it on. (USB Cable is sold separately)
- Press OPTION key and choose "DIRECT PRINTING FROM PC".
- Start installing the printer driver by clicking [Setup of the printer driver]



Stand Alone Mode

Changes your on-site work
faster and easier!



COMES WITH CARRY CASE

The durable plastic carry case comes with the LM550A machine holds extra ink ribbon cassettes and tape cassettes, which makes your on-site work a lot easier.



LARGE INTERNAL MEMORY

Maximum 250,000 letters can be saved on the internal memory. You don't have to worry about bringing external memory devices.

Internal Memory	Max. 250,000 characters (5,000 characters x 50 files)
Max. characters / file	5,000 characters
Max. number of file	50 files
Registration of words	30 files



INTEGRATED KEYBOARD

The printer has keyboard so you can edit marking contents at working site without a PC.



Professional Grade Features



LONGER ROLL LENGTH OF THE CONSUMABLES

LM-550A/PC adopts the dedicated consumables which have a longer roll length and save reloading time.

INK RIBBON	FORMER MODEL	50 meters	+ 60 meters
	LM-550A	110 meters	
TAPE CASSETTE	FORMER MODEL	8 meters	+ 8 meters
	LM-550A	16 meters	

*Black ink ribbon is 110m/roll, white ink ribbon is 70m/roll.

*LM-TP5xT (Transparent) and TP5xY (Yellow) remain as 8meters.



HIGH-SPEED MARKING

LM-550A/PC has an enhanced feeding system that provides you with marking speed at 40mm per second. With half cutting, it can make approx 52pcs of 20mm-long tube per minute.



TUBE PRINTING LENGTH IN 60 SECONDS

FORMER MODEL	35mm
LM-550A/PC	40mm


14% Faster



VERSATILE MARKING CAPABILITY

With LM-550A/PC you can print on wide variety of media in different sizes.

- PVC tubes $\phi 1.5\sim 8.0\text{mm}$
- Heat Shrinkable tubes $\phi 2.0\sim 6.5\text{mm}$
- MAX dedicated tapes (5mm/9mm/12mm wide)
- I.D. plates



LARGE BACKLIT LCD DISPLAY

The large backlit LCD display makes it easy to check input contents even in a dim work place.



WIDELY ADJUSTABLE PITCH LENGTH (Up to 60mm)




Tape : 4mm to 60mm Tube : 10mm to 60mm

*Auto pitch function is available for more than 60mm pitch

Useful Features


1 TUBE HEAD MARGIN SETTING

The length of initial tube head waste can be significantly reduced.




2 VERSATILE SEQUENCE SETTING

SERIAL NUMBER
1,2,3..



3 A VARIETY OF SYMBOLS FOR ELECTRICAL MARKING



ELECTRICAL SYMBOLS

MAX LETATWIN LM-550A/PC

4 LARGE INTERNAL MEMORY

LARGE RAM
250,000 CHARACTERS

Save print data inside the printer, and then you can recall data next time without entering data again.
(Maximum 250,000 characters /total 50 files)


5,000 characters x 50 = **250,000 characters**



5 WORD REGISTRATION



Frequently used words can be registered in the internal memory.
(Up to 30 words)



6 COPY & PASTE



You can copy and paste the input numbers and characters easily.



7 NUMERIC KEYPAD





The numeric keypad makes it easy to type numbers quickly and with only one hand.



8 PREVIEW FUNCTION




Before printing, you can check the printing contents on the LCD display, which decreases consumable loss due to mistyping, etc.



Advanced Settings

LM-550A/PC has lots of functions that are helpful to satisfy your various demands.


PRESS THIS BUTTON



▶▶ ADVANCED SETTINGS ①

Preferable Print Setting Registration


You are able to save up to 6 profiles for **PRINTING DENSITY**
POSITION OF PRINTING LINE
CUTTING POSITION
this makes it possible to set printing conditions for your specific demands.



▶▶ ADVANCED SETTINGS ②

Default Pitch Length Value


You can set the default value for the block pitch length.
Tape: 4 up to 60mm
Tube: 10 up to 60mm



▶▶ ADVANCED SETTINGS ③

Default Repeat Value


You can set default value for how many times a block is printed. Range : 2 - 100 pcs



▶▶ ADVANCED SETTINGS ④

Print Density


Choose between 8 settings for print density.



▶▶ ADVANCED SETTINGS ⑤

(6, 9) Under Bar Mark


The under-bar at the bottom of digit can be set for 6, 9.



▶▶ ADVANCED SETTINGS ⑥

Low Temperature Mode

In a low temperature environment, the printing result might not as good as a normal temperature environment. "LOW TEMP. MODE" can help improve print result quality in low temperature workplaces.




Printing Speed of Low Temp Mode: about 20mm/sec
(Normal Mode: about 40mm/sec)

LETATWIN
LM-550A/PC

▶▶ ADVANCED SETTINGS ⑦

Print Position Line


You can adjust it up and down.(-10 ~+12)



▶▶ ADVANCED SETTINGS ⑧

Cutting Position Adjustment

You can adjust the cutting position with changing right margin length. (Setting range: -2.0~+2.0mm)



Increase : Right margin increases. Decrease : Right margin decreases.

▶▶ ADVANCED SETTINGS ⑨

Automatic Power Off



When "YES" setting is applied, if no key is pressed for about 5 minutes, the machine turns off automatically.



▶▶ ADVANCED SETTINGS ⑩

Justification

Align your marker: LEFT, CENTER, RIGHT




▶▶ ADVANCED SETTINGS ⑪

Printing Style of "RPT" & "SEQ"

When repeating or sequencing, you can choose between "A : 11, 22, 33" or "B : 123, 123." printing styles

A : 11, 22, 33 →	01	01	02	02	03	03
B : 123, 123 →	01	02	03	01	02	03



Other Useful Features


LETATWIN LM-550A/PC



ECONOMICAL RE-FILL TYPE INK RIBBON



HALF-CUTTING WITH ADJUSTABLE DEPTH OF CUT



Depth of the half cut
can be adjusted.

SPECIFICATIONS

ITEMS	CONTENTS
Name	MAX ELECTRONIC LETTERING MACHINE LM-550A/PC
Dimensions	295 (W) × 293 (D) × 94 (H) mm
Weight	2.4kg
Printing method	Thermal transfer method (300dpi)
Display	LCD dot matrix : 64×160 Pixel (Backlit)
Printing speed	40mm/s (Standard) 20mm/s (Low temperature mode)
Maximum Printing length	Tube : 20m, Tape : 5m By multiple copy printing, maximum 30copies, upto Tube ; 100m, Tape ; 7m
Maximum number of characters to input	5,000 characters per file
Character size	1.3, 2, 3, 4, 6mm height
Usable tube	φ1.5mm ~ 8.0mm (PVC tube) (For φ1.5~2.0mm tubes, the dedicated attachment (standard accessory) is required.) φ2.0mm ~ 6.5mm (Heat Shrinkable tube)
Usable tape	Width 5, 9, 12mm (Max genuine tape)
Tube cutting method	Auto half cut, manual full cut
Internal memory	250,000 characters (Maximum 50 files)
External memory	USB memory
Interface	USB 2.0 full speed
Power supply	DC12V, 3.0A <small>Use only specified AC Adapter (100V~240V) Included in the package</small>
Power consumption	Max 30W
Operating environment	10°C to 35°C

PC REQUIREMENTS For Windows 10 / 8.1 / 8 / 7 operating systems. Windows® is a registered trademark of Microsoft Corporation(US) in U.S.A. or other countries.

The specifications and design of the products in this catalogue will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.

TUBE, TAPE and INK RIBBON

INK RIBBON CASE

20PCS/CTN

LM-RC500

ECONOMICAL INK RIBBON REFILLS

10 ROLLS/BOX

LM-IR50B (BLACK)

110m/ROLL

INK RIBBON REFILLS FOR HEAT SHRINKABLE TUBE

10 ROLLS/BOX

LM-IR50BP (BLACK)

110m/ROLL

LM-IR50W (WHITE)

70m/ROLL

TAPE CASSETTE

10PCS/BOX

LM-TP505W (WHITE)

5mm(W) × 16m(L)/PC

LM-TP505Y (YELLOW)

5mm(W) × 8m(L)/PC

LM-TP505T (TRANSPARENT)

5mm(W) × 8m(L)/PC

LM-TP509W (WHITE)

9mm(W) × 16m(L)/PC

LM-TP509Y (YELLOW)

9mm(W) × 8m(L)/PC

LM-TP509T (TRANSPARENT)

9mm(W) × 8m(L)/PC

LM-TP512W (WHITE)

12mm(W) × 16m(L)/PC

LM-TP512Y (YELLOW)

12mm(W) × 8m(L)/PC

UL RECOGNIZED TUBE

1ROLL/BOX

LM-TU332N2 WHITE

φ 3.2mm × 100m/ROLL

LM-TU336N2 WHITE

φ 3.6mm × 100m/ROLL

LM-TU342N2 WHITE

φ 4.2mm × 80m/ROLL

LM-TU352N2 WHITE

φ 5.2mm × 80m/ROLL

MAX HIGH QUALITY TUBE

1ROLL/BOX

LM-TU432L WHITE

φ 3.2mm × 200m/ROLL

LM-TU436L WHITE

φ 3.6mm × 200m/ROLL

LM-TU442L WHITE

φ 4.2mm × 200m/ROLL

LM-TU452L WHITE

φ 5.2mm × 135m/ROLL

LM-TU464L WHITE

φ 6.4mm × 100m/ROLL

LM-TU480L WHITE

φ 8.0mm × 70m/ROLL



MAX CO., LTD.

6-6, NIHONBASHI, HAKOZAKI-CHO, CHUO-KU, TOKYO, JAPAN
PHONE: 81-3-3669-8131 FAX: 81-3-3669-7104
Web: <http://www.max-ltd.co.jp/int/>

Distributor:



Lim Kim Hai Electric Co (S) Pte Ltd
Lim Kim Hai Building,
53 Kallang Place, Singapore 339177
T (+65) 6292 3711 • (+65) 6490 5000
F (+65) 6297 0078
E customerservice@limkimhai.com.sg
W www.limkimhai.com.sg