

The industrial smartwatch for ATEX/IECEx zones 1/21 for recording and displaying messages, hazard alarms and measured values. Coupled with i.safe MOBILE devices, it functions, for example, as a supplementary "hands-free" display. This makes the smartwatch highly flexible in use.

⁾ All trademarks and copyrights are the properties of their respective owners.) © 2022 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1062MD01REV02_EN_08.2022





IS-SW1.1



ATEX approval: Ex-Zone 1/21 Il 2G Ex ib IIC T4 Gb Il 2D Ex ib IIIC T135°C Db



IECEx approval: Ex-Zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db



UKEx approval: Ex-Zone 1/21 ⑤ II 2G Ex ib IIC T4 Gb ⑥ II 2D Ex ib IIIC T135°C Db

TECHNICAL FEATURES

Operating system ISM-OS

Memory 1 GB RAM | 8 GB internal memory

Dimensions size: 53,95 x 45,4 x 17,6 mm | weight: 70 g

Display 1,6" (4,064 cm) touchscreen | 320 x 360 pixels

Battery 500 mAh

Connections WiFi 2,4 GHz
Bluetooth® 5.1

GPS, Glonass, Beidou

Near Field Communication

Types of protection IP68 dust-/waterproof | MIL-STD-810H | usable from -20 °C to +55 °C

DISPLAY EXAMPLES











Clock

SOS Function

Pulse

SpO₂

FURTHER FEATURES



Collecting vital data like SpO₂, Pulse



SOS key for loneworker protection LWP ready (third party application required, based on country specific regulations)



Vibration alarm



Accelerometer, gyroscope, magnetic, pressure sensors

SET CONTENT

Smartwatch, Desktop Charger, Power Adapter universal, i.safe PROTECTOR 2.0, Screwdriver, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.