

**PZ 6 ROTO ADJ****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Crimping tools for wire end ferrules, with and without plastic collars**

- Ratchet guarantees precise crimping
- Release option in the event of incorrect operation

**General ordering data**

|            |                                                            |
|------------|------------------------------------------------------------|
| Version    | 0.14mm <sup>2</sup> , 6mm <sup>2</sup> , Trapezoidal crimp |
| Order No.  | <a href="#">2831380000</a>                                 |
| Type       | PZ 6 ROTO ADJ                                              |
| GTIN (EAN) | 4064675415909                                              |
| Qty.       | 1 pc(s).                                                   |

## PZ 6 ROTO ADJ

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |        |                |            |
|------------|--------|----------------|------------|
| Width      | 200 mm | Width (inches) | 7.874 inch |
| Net weight | 425 g  |                |            |

## Environmental Product Compliance

|            |                |      |                                      |
|------------|----------------|------|--------------------------------------|
| REACH SVHC | Lead 7439-92-1 | SCIP | 2159813b-98fd-4068-b62a-bc89a046c012 |
|------------|----------------|------|--------------------------------------|

## Technical data

|                        |                  |         |                                             |
|------------------------|------------------|---------|---------------------------------------------|
| Description of article | (1)Crimping tool | Version | Mechanical, without interchangeable inserts |
|------------------------|------------------|---------|---------------------------------------------|

## Description of contact

|                                   |                                                |                                   |                      |
|-----------------------------------|------------------------------------------------|-----------------------------------|----------------------|
| Conductor cross-section, max. AWG | AWG 10                                         | Conductor cross-section, min. AWG | AWG 26               |
| Crimping range, max.              | 6 mm <sup>2</sup>                              | Crimping range, min.              | 0.14 mm <sup>2</sup> |
| Type of contact                   | Wire-end ferrules with/without plastic collars |                                   |                      |

## tool data crimping

|                       |                   |
|-----------------------|-------------------|
| Crimping type/profile | Trapezoidal crimp |
|-----------------------|-------------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000168    | ETIM 7.0    | EC000168    |
| ETIM 8.0    | EC000168    | ECLASS 9.0  | 21-04-38-11 |
| ECLASS 9.1  | 21-04-38-11 | ECLASS 10.0 | 21-04-38-11 |
| ECLASS 11.0 | 21-04-38-11 | ECLASS 12.0 | 21-04-38-11 |



Lim Kim Hai Electric Co (S) Pte Ltd  
 Lim Kim Hai Building,  
 53 Kallang Place, Singapore 339177  
 T (+65) 6292 3711 • (+65) 6490 5000  
 F (+65) 6297 0078  
 E customerservice@limkimhai.com.sg  
 W www.limkimhai.com.sg