

SIM card -
easy to install



**ZONE 1/21
CL I, II, III DIV 1**



› Ideal for IoT maintenance applications

› Zero-touch capable

› Android™ 13

IS930.1

Android
Enterprise
Recommended



The robust and powerful tablet of the Industry 4.0 generation is Android Enterprise Recommended and, thanks to its zero-touch functionality, can be used quickly and is ideally suited for maintenance applications in the IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap and a separate leather bag with a shoulder/belt or carry strap system are further highlights.

› Android is a trademark of Google LLC. All trademarks and copyrights are the properties of their respective owners. › © 2023 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1030MD01REV16_EN_03.2024



< IS930.1 >



ATEX approval: EX-Zone 1/21
Ⓜ II 2G Ex ib IIC T4 Gb
Ⓜ II 2D Ex ib IIIC T135°C Db IP6X



IECEx approval: EX-Zone 1/21
Ex ib IIC T4 Gb
Ex ib IIIC T135°C Db IP6X



NEC500 approval:
Class I, II, III Division 1
Groups A B C D E F G T4



EAC approval:
1Ex ib IIC T4 Gb X
Ex ib IIIC T135°C Db X IP6X

Further approvals: INMETRO (Brazil) | KCs (South Korea) | PCEC (China) | JNIOOSH (Japan) | SANS (South Africa)

TECHNICAL FEATURES

Operating system	Android™ 13
Processor	SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz)
Memory	4 GB RAM 64 GB internal memory microSD memory up to 512 GB
Frequencies	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39
Dimensions	size: 237 x 156 x 22 mm weight: 890 g
Display	8" Gorilla Glass® 3. generation 1200 x 1920 pixels
Battery	8400 mAh
Camera	13 MP AF rear camera 5 MP FF front camera
Connections	WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot Bluetooth® 5 GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication
Types of protection	IP68 dust-/waterproof MIL-STD-810H usable from -20 °C to +60 °C

FURTHER FEATURES



SOS key for loneworker protection
LWP ready (third party application required,
based on country specific regulations)



2 freely programmable keys



Usable with gloves



Accelerometer, gyroscope, magnetic,
temperature and humidity, proximity sensors



Magnetic charger port

SET CONTENT

Tablet with integrated battery, Hand Strap, i.safe PROTECTOR 2.0 Type C USB Cable, i.safe PROTECTOR 3.0 USB Magnetic Charger Cable, Power Adapter universal, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.