

Cypress

120-160kW DC Super-fast Charger

CE CB UK TR25 AD RoHS

Product description

Tailored for the global market, this product boasts enhanced data processing capabilities and a more sophisticated dispatching strategy. It seamlessly integrates with high-power charging systems for vehicles featuring CCS/CHAdeMO/GBT interfaces. Utilizing precise control algorithms and thermal simulations, it significantly reduces charging system noise. Furthermore, it offers compatibility with 99.9% of electric vehicle models, catering to the charging requirements of diverse electric vehicles.

- Supports remote fault diagnosis and controller OTA upgrade.
- DC output range of 200-1000V, system power coverage range of 30-400kW, suitable for a wide range of electric vehicles.
- Excellent high temperature performance, ensure full load operation and fast charging.
- Multiple protection design to ensure the safety of drivers and vehicles.
- Intelligent HMI, support a variety of communication interfaces, easy to operate.
- Multi-region linkage sampling ensures comprehensive data collection across diverse environments, safeguarding system integrity and performance.



Application Scenarios

- Taxi, online-hailing cars
- Bus
- Public charging station
- Residence community
- Customized shuttle bus
- Freight vehicles Special vehicles
- Enterprises and institutions
- Commercial complex

Item	Parameters		
------	------------	--	--

Basic index

Model	YLUXD120KE	YLUXD150KE	YLUXD160KE
Rated power	120kW	150kW	160kW
Dimensions (WxDxH)	850x610x2200mm		
Weight (KG)	≤350KG		
Charging outlet	CCS/CHAdeMO/GBT, length: 5m (customized)		
HMI	10.1-inch color touch screen		
Energy meter	MID		
Installation	Ground mounted		

Payment

Payment mode	RFID/Credit Card/Scan QR code (optional)
--------------	--

Input

voltage	400VAC±10%,3P+N+PE		
Frequency	45Hz-65Hz		
Current	184A	230A	246A
Power factor	≥0.99		
ITHD	≤5%		

Output

Voltage	200-1000Vdc		
Current	CCS2 200A max. CHAdeMO 125A max.		
Power	CCS2 120kW max. CHAdeMO 62.5kW max.	CCS2 150kW max. CHAdeMO 62.5kW max.	CCS2 160kW max. CHAdeMO 62.5kW max.
Max efficiency	>95%		
Charging way	Meantime		

Environment

Operating temperature	-30 ~ +50°C
Humidity	5%~95%RH, non-condensing
Altitude	≤2000m no derating required;>2000m,the working temperature decreases by 1 ° C for every 100m rise
Protection Grade	IP54
Application Site	Indoor/Outdoor
Cooling method	Fan cooling
Noise (lab environment)	≤60dB

Standards & certifications

EVSE	PLC (DIN 70121: 2014-12 / ISO15118)
Back-end protocol	Ethernet, 4G, OCPP 1.6J
Certification	CE & CB & UKCA & TR25&ADQCC&RCM