

TABLET ZONE 2/22

IS940.2



APPROVALS



ATEX approval: EX-Zone 2/22 requested
 Ⓜ II 3G Ex ic IIC T4 Gc
 Ⓜ II 3D Ex ic IIIC T135°C Dc



IECEx approval: EX-Zone 2/22 requested
 Ex ic IIC T4 Gc
 Ex ic IIIC T135°C Dc



NEC500 Zulassung: requested
 Class I, II, III Division 2
 Groups A B C D F G T4

TECHNICAL FEATURES

Model M940A01

OPERATING SYSTEM	Android™ 14
PROCESSOR	Qualcomm® QCM6490 Octa Core
MEMORY	8 GB RAM 128 GB internal memory microSD card supported
SUPPORTED FREQUENCY BANDS	4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFB1/13/14/17/20/25/26/28A/28B/29/30/66/68/71 4G LTE-TDD: B38/39/40/41/42/43/48 5G NR: n1/n2/n3/n5/n7/n8/n12/n14/n20/n25/n28/n30/n38/n40/n41/n48/n66/n71/n77/n78/n79
DIMENSIONS	Size: 266,17 x 168,46 x 19,82 mm weight: 1059 g
DISPLAY	10,1" (25,65 cm) Corning® Gorilla® Glass 3rd generation 1200 x 1920 pixels usable with gloves
BATTERY	8160 mAh replaceable
CAMERA	50 MP AF rear camera 5 MP FF front camera
SIM SUPPORT	1 nano SIM + eSIM
CONNECTIONS	Wi-Fi® 6: IEEE 802.11 a/b/g/n/ac/ax/e/k/r/v Bluetooth® 5.2 GPS, A-GPS, Glonass, A-Glonass, Beidou, Galileo Near Field Communication (NFC)
PORTS IN/OUT	16-pin ISM interface 12-pin ISM interface (Docking Station: optional accessory) USB-C
SENSORS	Accelerometer, Gyroscope, Light, Magnetic, Proximity, Pressure sensors
TYPES OF PROTECTION	IP68 dust-/waterproof MIL-STD-810H usable from -20 °C to +55 °C

FURTHER FEATURES

FUNCTION KEY RED	Optional functions assignable via System App, e.g. LWP
FUNCTION KEYS RIGHT	Optional functions assignable via Button App (system integrated)
MOUNTING	VESA 100
AMPLIFIED LOUDSPEAKER	

SET CONTENT

Tablet, Battery, Hand Strap, USB-C Cable, Power Adapter universal, Screwdriver, Display Protection Foil and Safety Instructions



Lim Kim Hai Electric Co (S) Pte Ltd
 Lim Kim Hai Building,
 53 Kallang Place, Singapore 339177
 T (+65) 6292 3711 • (+65) 6490 5000
 F (+65) 6297 0078
 E customerservice@limkimhai.com.sg
 W www.limkimhai.com.sg